

## WE10 Key Features



## Outstanding performance

The high performance CMOS scan engine means the scanning of the WE10 is accurate and the speed is fast. It is up to the national secondary laser safety standards and offers incredibly stable reliable scanning

## Advanced protection

Up to an IP67 sealing means the WE10 can be washed directly with tap water without interfering with the scanners operation. Also able to withstand drops of 5m, the WE10 is robust enough to handle the toughest working environments.

## Comfortable and practical

The comfortable hand grip of the BCX-WE10 has been designed with a perfect curvature so it fits nicely into the hand, thus reducing user fatigue over periods of continual use.

Not only is the scanner aesthetically pleasing but it has been built to last; the high rebound scan trigger is both comfortable and durable and can withstand being pressed millions of times without jamming. The clear audio and visual good read indicators enable fast, uninterrupted scanning no matter the environment.



## Applications

Ideal for logistics - medical - clothing - manufacturers - supermarkets/stores - food.



# Comet WE10

## 2D Tough barcode scanner

### WE10 Technical Specification

Voltage	5V±0.25V DC
Light source	5600K white
Resolution	1280 x 800 (1MP)
Scanning angle	±360°, ±40°, ±40°
Scanning precision	QR ≥7mil, Code128 ≥4mil, Code39 ≥4mil
Scanning depth	Code39 (5mil) 60-120mm; IPC/EAN (15mil) 35-310mm
Codes read	1D: EAN 13/EAN8, UPCA.UPCE, Code128, Code39, Code11, Code93, Code32, Coda Bar Interleaved 2 of 5, Plessey, MSI, Pharmacode, IATA 2 of 5, Composite Code-A, Composite Code-B, Composite Code-C, RSS-14, RSS-14 expanded, RSS-14 Limited, Straight 2 of 5. 2D: QR code, Data Matrix, PDF417, Aztec Code, Micro PDF417, Micro QR, MaxiCode
Printing contrast ratio	≥30%
Promoting mode	Buzzer, LED indicator light
Interface	USB, RS-232 serial port, USB-COM
Scanning mode	Manual, continuous, automatic
Shell material	Two colour accessories: ABS+PC/TPU, Monochrome: ABC+PC, Transparent parts: PC
Working temperature	0°C~50°C
Storage	-40°~70°C
Relative humidity	5%~95% (non-condensing)
IP rating	IP65 and IP67
Drop test	Can resist the fall impact from 5m
Setting way	Scanning the setting codes in turn
Product size	185mm x 75mm x 95mm
Net weight	294g
Gross weight	520g