VMAX EDGE Series Touch Terminal

The VMAX EDGE Series is a high-performance 15" and 15.6" touchscreen POS terminal designed for speed, reliability, and everyday commercial use. Featuring Intel Celeron J6412 or Intel Core i7 processor options, the EDGE delivers powerful processing capability combined with a bright, high-quality LCD panel and responsive 10-point PCAP touch technology. Built for demanding retail and hospitality environments, the EDGE provides robust connectivity and flexible expansion options in a sleek, professional design.

High-Speed Processing Performance
The EDGE Series offers powerful Intel processor options to ensure fast transaction processing and smooth multitasking, even in busy environments. With flexible memory and storage configurations, it can be tailored to suit both standard and high-performance POS applications.

Bright & Responsive Touch Display
Equipped with a high-quality LCD panel and projected capacitive touchscreen, the EDGE delivers a clear, responsive user experience. Its commercial-grade brightness ensures visibility in a variety of lighting conditions.

Flexible Expansion & Optional Additions
With support for multiple optional accessories and upgrade paths, the EDGE Series adapts to changing business requirements. From rear displays to removable SSD storage, it offers scalable flexibility.

Extensive Connectivity & I/O Options
The EDGE provides a wide range of standard ports to support POS peripherals, payment devices, and network connectivity. Designed for integration, it easily fits into new or existing POS setups.

EDGE VT1500-V Technical Specification

Model	VT1500-VJB/VT1560-VJB	VT1500-Vi7/VT1560-Vi7
Processor	Intel Celeron J6412	Intel Core i7-1065G7
System Memory	DDR4 8BG (16GB/32GB optional)	DDR4 8BG (16GB/32GB optional)
Storage Device	mSATA 128GB (up to 1TB optional)	mSATA 128GB (up to 1TB optional)
Supported OS	Windows 10 or 11 LTSC/Linux	Windows 10 or 11 LTSC/Linux
Dispaly & Touch		
LCD	15-inch/15.6-inch	15-inch/15.6-inch
Resolution	1024 x 768/1366 x 768	1024 x 768/1366 x 768
Touch	10-Point PCAP	10-Point PCAP
Brightness	350nts	300nts
IO/Ports		
Standard Ports	DC Port "1, HDMI"1, COM*1, LAN"1, USB3.0"2, LINE-OUT+ MIC*1 RJ11 CD. RI45-COMM*3	DC Port »1. HDMI"1. COM*1, LAN"1, USB3.0"2, LINE-OUT+ MIC*1 RJ11 CD. RI45-COMM*3
Power		
Power Adapter	DC 12V 5A	DC 12V 5A
Environmental		
Operating Conditions	0°C - 50°C 20%RH - 90%RH	0°C - 50°C 20%RH - 90%RH
Optional		
Optional Additions	Removable SSD Slot, Speaker, Secondary 11.6" LCD Rear Display, 2 Line VFD, MSR. I_Button. PoE LAN Support	